

SANME

PP 系列轮式移动破碎站

PP Series Portable Crushing Plants

德国技术

German Technology



上海山美重型矿山机械有限公司 (德国哈兹马克合资公司)
SHANGHAI SANME MINING MACHINERY CO., LTD. (JV WITH HAZEMAG GERMANY)



山美矿机 您的良机

上海山美重型矿山机械有限公司是中国领先的破碎筛分设备制造商，是德国哈兹马克公司在中国的合资公司。拥有现代化的加工制造能力和由优秀的工程师组成的研发队伍，积多年的专业经验所开发的 PP 系列轮式移动破碎站具有国际先进水平，PP 系列轮式移动破碎站在矿物加工、砂石骨料生产和建筑废物处理等领域得到广泛应用，并已经出口到世界上三十多个国家和地区。

Shanghai Sanme Mining Machinery Co.,Ltd is a leading manufacturer of crushing and screening equipments in China, a joint venture with HAZEMAG Germany. Our company has modern manufacturing capability and excellent R&D teams of professional engineers. Based on our decades experience in crushing and screening field, PP Series Portable Crushing and Screening Plants have reached the international advanced level. PP Series Portable Crushing Plants are widely used in minerals processing, aggregates processing, construction waste recycling and other fields. They have been exported to more than 30 countries in the world.



具有世界先进水平、能够为您创造更大价值的

PP 系列轮式移动破碎站

Of World Advanced Level, Creates Greater Value For The Customers
PP Series Portable Crushing Plants

产品系列 Product Presentation

颚式破碎站 Jaw Plants

PP600
PP750
PP900
PP1060
PP1200

圆锥式破碎站 Cone Plants

PP120SMH(S)
PP180SMH(S)
PP250SMH(S)

反击式破碎站 Impact Plants

PP139HC(S)
PP239HC(S)
PP255HC(S)

立式冲击破碎站 VSI Plants

PP5000VSI(S)
PP6000VSI
PP7000VSI





PP 系列轮式移动破碎站采用最新的移动破碎技术，能够完全满足客户的移动破碎要求，同固定式破碎设备相比较，能够大大降低客户的运营成本。

PP Series Portable Crushing Plants adopt the latest mobile crushing technology. They can fully meet customers' different mobile crushing requirements. Compared with the stationary crushing plant, they can greatly reduce the customers' operation cost.



PP系列轮式移动破碎站具有如下优异性能：

The Outstanding Performance of PP Series Portable Crushing Plants :



移动性强：

PP 系列轮式移动破碎站长度短，不同的破碎设备分别安装在独立的可移动底盘上，轴距短，转弯半径小，可以在普通公路上及作业厂区内灵活行驶。

Great Mobility :

PP Series Portable Crushing Plants are of short length. Different crushing equipment is separately installed on a separate mobile chassis. Its short wheelbase and tight turning radius mean they can be transported on highway and moved at crushing sites.



降低物料运输成本：

PP 系列轮式移动破碎站可以在现场加工物料，而不必将物料搬离现场再加工，大大地降低了物料的运输成本。

Lower Transportation Cost :

PP Series Portable Crushing Plants can crush materials on-site. It is unnecessary to carry the materials from one site and then crush them in another one, which can greatly lower the transporting cost for off-site crushing.



组合灵活，适应性强：

PP 系列轮式移动破碎站可根据不同的破碎工艺要求组成“先碎后筛”，也可组成“先筛后碎”流程，破碎站可按实际需求组合成粗碎、细碎两段破碎筛分系统，也可组合成粗碎、中碎、细碎三段破碎筛分系统，还可以独立运行，有很大的灵活性。

Flexible Configuration and Great Adaptability:

According to the different requirements of different crushing process, PP Series Portable Crushing Plants can form the following two processes of “crushing first, screening second” or “screening first, crushing second”. The crushing plant can be composed of two-stage plants or three-stage plants. The two-stage plants consists primary crushing plant and secondary crushing plant, while the three-stage plants includes primary crushing plant, secondary crushing plant and tertiary crushing plant, each of which is of high flexibility and can be used individually.

PP系列轮式移动破碎站具有如下设计特点：

The Design Features of PP Series Portable Crushing Plants :



移动底盘设计符合国际标准，拥有符合规范的灯光和制动系统。底盘采用大截面型钢，为重载设计。

Mobile chassis conforms to the international standards. It has standard lighting and braking system. The chassis is heavy-duty design with big section steel.



移动底盘采用 U 型梁设计，降低了移动站的整体高度，大大降低了破碎物料的装运成本。

The girder of mobile chassis is designed to be U style so that the overall height of the mobile crushing plant is reduced. So the loading cost is reduced greatly.



采用液压支腿（选装），便于现场安装；料仓采用组合设计，大大降低运输高度。

Adopt hydraulic leg(optional) for lift installation. Hopper adopt unitized design, reduce the transport height greatly.



PP系列移动颚式破碎站

PP Series Portable Jaw Crushers

PP 颚式破碎站 PP Jaw Crushers	PP600	PP750	PP900	PP1060	PP1200
运输尺寸 Transport dimensions					
长 Length (mm)	8600	9600	11097	13300	15800
宽 Width (mm)	2520	2520	3759	2900	2900
高 Height (mm)	3770	3500	3500	4440	4500
重量 Weight (kg)	15240	22000	32270	57880	98000
轴重 Axle weight (kg)	10121	14500	21380	38430	64000
牵引销荷重 King pin weight (kg)	5118	7500	10890	19450	34000
颚式破碎机 Jaw Crusher					
型号 Model	PE400x600	PE500x750	PE600X900	PE750x1060	PE900x1200
给料口 Feed opening (mm)	400x600	500x750	600X900	750X1060	900x1200
出料口调整范围 Setting range(c.s.s)(mm)	40-100	50-100	65-180	80-180	95-225
产量 Capacity (m ³ /h)	10-35	25-60	30-85	70-150	100-240
给料机 Feeder					
型号 Model	GZT0724	GZT0724	GZT0932Y	ZSW490x110	ZSW600x130
料仓容积 Feed hopper volume (m ³)	3	4	7	10	10
料仓宽 Hopper width (mm)	2200	2500	3000	3000	3000
皮带机 Belt Conveyor					
型号 Model	B650 × 6	B800 × 7	B1000 × 8	B1000 × 11	B1200 × 13



PP系列移动圆锥式破碎站

PP Series Portable Cone Crushers

PP 圆锥式破碎站 PP Cone Crushers	PP120SMHS	PP180SMHS	PP180SMH	PP250SMHS	PP250SMH
运输尺寸 Transport dimensions					
长 Length (mm)	11200	11800	10000	12300	10816
宽 Width (mm)	2743	2743	2480	2900	2743
高 Height (mm)	4200	4200	4160	4200	4160
重量 Weight (kg)	28400	30500	22400	48700	35700
轴重 Axle weight (kg)	15500	16300	14300	31100	22900
牵引销荷重 King pin weight (kg)	12900	14200	8100	17600	12800
圆锥破碎机 Cone Crusher					
型号 Model	SMH120	SMH180	SMH180	SMH250	SMH250
最大进料 Feed opening (mm)	160	180	180	240	240
出料口调整范围 Setting range(c.s.s)(mm)	22-32	22-32	22-32	26-51	26-51
振动筛 Screen					
型号 Model	2/3YK1545	2/3/4YK1548		2/3/4YK1848	
皮带机 Belt Conveyor					
型号 Model			B800 × 8		B1000 × 8



PP系列移动反击式破碎站（初碎） PP Series Portable Impact Crushers (Primary)

PP 反击式破碎站（初碎） PP Impact Crushers (Primary)	PP139HC	PP239HC	PP255HC
运输尺寸 Transport dimensions			
长 Length (mm)	10800	11400	11490
宽 Width (mm)	2780	2780	2880
高 Height (mm)	4170	4300	4470
重量 Weight (kg)	30	39.3	46.3
轴重 Axle weight (kg)	19	24.6	30.1
牵引销重 King pin weight (kg)	11.0	14.7	16.2
反击式破碎机 Impact Crushers			
型号 Model	HC139	HC239	HC255
给料口 Feed opening (mm)	1100 × 630	1100 × 740	1450 × 760
产量 Capacity (t/h)	90–150	130–200	180–250
给料机 Feeder			
型号 Model	GZT0724	GZT0932	ZSW3895
料仓容积 Feed hopper volume (m ³)	3.2	7.6	9
皮带机 Belt Conveyor			
型号 Model	B800	B800	B1000
永磁自卸式除铁器 Permanent Magnetic Separator			
除铁器 Magnetic separator	选装 optional	选装 optional	选装 optional



PP系列移动反击式破碎站(中碎)

PP Series Portable Impact Crushers (Secondary)

PP 反击式破碎站 (中碎) PP Impact Crushers (Secondary)	PP139HCS	PP239HCS	PP255HCS
运输尺寸 Transport dimensions			
长 Length (mm)	10800	12200	12500
宽 Width (mm)	2480	2743	2900
高 Height (mm)	4170	4200	4200
重量 Weight (kg)	28800	31500	39600
轴重 Axle weight (kg)	15900	17200	22100
牵引销重 King pin weight (kg)	11300	14300	17500
反击式破碎机 Impact Crusher			
型号 Model	HC139	HC239	HC255
给料口 Feed opening (mm)	1100 × 640	1100 × 740	1450 × 760
振动筛 Screen			
型号 Model	2/3/4YK1235	2/3/4YK1545	2/3/4YK1548



PP系列移动立式冲击破碎站

PP Series VSI Plants

PP 立式冲击破碎站 PP VSI Plants	PP5000VSI	PP5000VSIS	PP6000VSI	PP7000VSI
运输尺寸 Transport dimensions				
长 Length (mm)	98000	11280	10180	11180
宽 Width (mm)	2460	2780	2780	2780
高 Height (mm)	4200	2500	4200	4316
重量 Weight (kg)	21600	32000	24600	33650
轴重 Axle weight (kg)	14600	18800	16500	23263
牵引销荷重 King pin weight (kg)	7000	13200	8100	10387
立式冲击破碎机 VSI Crusher				
型号 Model	VSI-5000	VSI-5000	VSI-6000	VSI-7000
最大给料尺寸 Max feed size (mm)	65 (80)	65 (80)	80 (100)	80 (100)
通过量 Throughput capacity range (t/h)	80-150	80-150	120-250	140-250
振动筛 Screen				
型号 Model		2/3YK1545		
皮带机 Belt Conveyor				
型 号 Model	B650 × 6.5		B800 × 7	B1000 × 7.2



上海山美重型矿山机械有限公司 (德国哈兹马克合资公司)
SHANGHAI SANME MINING MACHINERY CO., LTD. (JV WITH HAZEMAG GERMANY)



版权所有 翻印必究 中国印制 Printed in China SANME-07C | PP | 2012-11 | 5000

地址: 上海市奉贤区青村镇奉村路 258 号
邮编: 201414
电话: 021-5759 1166 5759 1188
传真: 021-5756 6188 5820 0089
网址: www.shsmzj.com
电邮: info@sanmecrusher.com

Add: No.258, Fengcun Road, Qingcun County,
Fengxian District, Shanghai 201414, China
Tel: +86-21-5712 1166 5759 1188
Fax: +86-21-5756 6188 5820 0089
Website: www.sanmecrusher.com
E-mail: sales@sanmecrusher.com

免费热线: 400 921 5566
售后专线: 021-5712 7766

Free Hotline: 400 921 5566
Service Center: +86-21-5712 7766

◎我们的产品在不断的更新和改进中, 我们保留在未事先告知用户的情况下, 更改参数及设计的权利。

Our products are constantly updated and improved, we reserve the right to change parameters and design without advance notification of customers.

◎照片中产品外观颜色与实际机型存在差异, 颜色标准以实物为准。

If there are any discrepancy and difference between color of product appearance and actual machine type in the picture, color standard is subject to actual object.

◎本手册中的配置不一定是出厂标准配置, 购买时请详细咨询经销商。

Specifications and design in the brochures are not always the standard. Please consult our dealers or distributors particularly when purchasing.